

Electric Vehicle SLA Battery

EVX SERIES

Bosfa EVX Series batteries are designed to have a large amount of stored current discharged between charging sessions, with very heavy non-porous battery plates to withstand repeated major discharging and charging cycle (deep cycles). The Bosfa EVX batteries uses a different chemistry for the plates active paste material, and a slightly stronger electrolyte than normal battery electrolyte, which allows for a much longer life in deep cycle applications.

Application

- Electric Powered Vehicles
- Golf Cars and Buggies
- Wheel Chairs
- Power Tools





- Electric Powered Toys
- Control System
- Vacuum Cleaners
- Medical Equipments
- UPS
- Pvs

General Features

- Sealed and maintenance free operation.
- Non-Spillable construction design.
- ABS containers and covers(UL94HB, UL94V-0) optional.
- Safety valve installation for explosion proof.
- High quality and high reliability.
- Exceptional deep discharge recovery performance.
- Low self discharge characteristic.
- Flexibility design for multiple install positions.


Construction

- ComponentRaw material
- PositiveLead dioxide
- NegativeLead
- ContainerABS
- CoverABS
- SealantEpoxy Resin
- Safety valveEPDR
- TerminalCopper
- SeparatorFibre glass
- ElectrolyteSulfuric acid

**Terminal Dimensions**

Battery Model	EVX 36-10.5			
Designed Cycle Life	> 350 cycles @ 100% DOD			
Capacity(25°C)	20HR(0.525A,1.75V)	10HR(0.95A,1.75V)	2HR(3.6A,1.75V)	1HR(6.3A,1.75V)
	10.5AH	9.5AH	7.2AH	6.3AH
Dimensions	Length	Width	Height	Total Height
	190mm(7.48inch)	150mm(5.91inch)	100mm(3.94inch)	100mm(3.94inch)
Approx. Weight	8.6Kg (18.96lbs)			
Internal Resistance	Full charged at 25°C: 0.06 Ohm			
Self Discharge	3% of capacity declined per month at (25°C)			
Capacity Affected by Temp.(20HR)	40°C	25°C	0°C	-15°C
	102%	100%	85%	65%
Charge Voltage(25°C)	Cycle use		Float use	
	44.4V(-90mV/ °C), max. Current: 3A		41.4V(-60mV/ °C)	

Electric Vehicle SLA Battery



Constant current discharge ratings-amperes at 25°C

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	5HR	10HR	20HR
1.60V	41.0	25.5	19.3	11.7	7.46	4.10	2.00	1.07	0.59
1.67V	38.5	24.2	18.5	11.2	7.36	3.94	1.96	1.06	0.57
1.70V	35.3	23.3	18.1	10.2	7.14	3.68	1.92	1.05	0.56
1.75V	34.6	22.6	17.5	9.70	6.80	3.55	1.88	1.04	0.54
1.80V	30.9	21.6	15.9	8.98	6.37	3.41	1.76	1.02	0.53
1.85V	27.3	20.6	14.3	8.27	5.94	3.29	1.65	1.01	0.52

Constant power discharge ratings-watts at 25°C

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	5HR	10HR	20HR
1.60V	72.0	46.1	35.1	21.1	13.5	7.26	3.38	2.13	1.18
1.67V	69.4	44.9	34.7	20.7	13.4	7.04	3.37	2.12	1.13
1.70V	65.4	44.5	34.4	19.4	13.1	6.72	3.33	2.11	1.12
1.75V	65.8	44.3	34.1	18.8	12.9	6.56	3.30	2.08	1.09
1.80V	60.2	43.7	31.6	17.9	12.2	6.37	3.19	2.05	1.06
1.85V	54.6	41.4	28.7	16.8	11.4	6.18	3.09	2.03	1.02

